

PHOTOMULTIPLIER TUBE

TYPE : R6357 SEL

CUSTOMER: UNIV OF CALIF SAN DIEGO

QUANTITY: 2 pcs.

Serial Number	(1) Cathode Luminous Sens.	(2) Anode Luminous Sens.	(3) Anode Dark Current	(4) R/W	(5) Cathode Blue Sens. Index		
	μ A/lm	A/lm	nA	$\times 10^{-3}$			
MAC5548	449.0	1470.0	0.80	303.0	15.90		
MAC5896	393.0	1840.0	1.20	331.0	13.20		

NOTES

- (1) (2) (4) (5) Light source : Tungsten filament lamp operated at 2856 K.
- (2) (3) Overall supply voltage : 1000 V
- Voltage distribution : The standard voltage distribution ratio listed in the HAMAMATSU photomultiplier catalog.
- (3) The bulb of the tube is insulated from ground potential.
- (4) The quotient of the red light sensitivity (measured with a Toshiba R-68 red filter) divided by the white light sensitivity.
- (5) Measured with a Corning CS 5-58 blue filter (half stock thickness).

Date: OCTOBER 10, 2013

Approved by : *T. Haranoya*

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Electron Tube Division
314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone : (81)0539-62-5248, Fax : (81)0539-62-2205