


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED



DRILL CHART: TOP to BOTTOM			
ALL UNITS ARE IN MILS			
FIGURE	SIZE	PLATED	QTY
+	16.0	PLATED	57
o	35.0	PLATED	174
o	61.0	PLATED	4
o	67.0	PLATED	16
o	120.0	PLATED	2

1. ALL LAYERS ARE VIEWED FROM COMP SIDE
2. HOLE DIAMETER IS AFTER PLATING
3. TYPE FR4 MATERIAL WITH 1 Oz. COPPER LAYERS
4. FINISHED BOARD THICKNESS 0.062 INCH
5. SILK SCREEN COMP SIDE USING WHITE EPOXY INK
6. FINISH: SOLDER PLATED
7. SOLDER MASK BOTH SIDES WITH LIQUID PHOTO IMAGEABLE MASK COLOR GREEN OVER BARE COPPER
8. EDGE CONNECTOR SOLDER PLATED & BEVELED

UNLESS OTHERWISE SPECIFIED	SIGNATURES	DATE	UCSD PHYSICS DEPARTMENT			
DIMENSIONS ARE IN INCHES TOLERANCES ON: 2 PL DECIMALS + 3 PL DECIMALS + ANGLES + FRACTIONS +			2 CHANNEL PMT AMPLIFIER			
			WITH SELECTABLE GAIN/OFFSET			
			SIZE	FSCM NO	DWG NO	PHY-DK-F040415-S1
			SCALE			SHEET 1 OF 1